

# 1/C AL 35kV 420 NLEPR 133% Thermoplastic LSZH-TP MV-105

Type MV-105 Single Conductor Copper, 420 Mils No Lead Ethylene Propylene Rubber (NL-EPR) 133% Insulation Level, Tape Shield, Thermoplastic SOLONON® Low Smoke Zero Halogen (LSZH-TP) Jacket, Rated UL. Silicone Free




Image not to scale. See Table 1 for dimensions.

## CONSTRUCTION:

1. **Conductor:** Class B compact stranded 8000 Series aluminum per ASTM B800 and ASTM B836
2. **Conductor Shield:** Semi-conducting cross-linked copolymer; A conductor separator is used for cable size larger than or equal to 500 Kcmil
3. **Insulation:** 420 Mils No Lead Ethylene Propylene Rubber (NL-EPR) 133% Insulation Level,
4. **Insulation Shield:** Strippable semi-conducting cross-linked copolymer
5. **Copper Tape Shield:** Helically wrapped 5 mil copper tape with 25% overlap
6. **Overall Jacket:** Thermoplastic SOLONON® Low Smoke Zero Halogen (LSZH-TP)

## APPLICATIONS AND FEATURES:

Southwire's 35KV cables are suited for use in wet and dry areas, conduits, ducts, troughs, trays, direct burial when installed with a grounding conductor in close proximity that conforms to NEC section 311.36 and 250.4(A)(5), and where superior electrical properties are desired. These cables are capable of operating continuously at the conductor temperature not in excess of 105°C for normal operation, 140°C for emergency overload, and 250°C for short circuit conditions. Rated at -35°C for cold bend. ST1 (low smoke) Rated for sizes 1/0 and larger. Rated for 1000 lbs./FT maximum sidewall pressure.

## SPECIFICATIONS:

- ASTM B801 Concentric-Lay-Stranded Conductors of 8000 Series Aluminum Alloy
- UL 1072 Medium-Voltage Power Cables
- UL 1685 FT4-ST1 Vertical-Tray Fire Propagation and Smoke Release Test (1/0 and Larger)
- ICEA S-93-639 (NEMA WC 74) 5-46 KV Shielded Power Cable
- IEEE 1202 FT4 Flame Test (70,000) BTU/hr Vertical Tray Test (1/0 and Larger)
- AEIC CS-8 Specification for extruded dielectric shielded power cables rated for 5 through 46KV
- Made in America: Compliant with both Buy American and Buy America Act (BAA) requirements per 49 U.S.C. § 5323(j) and the Federal Transit Administration Buy America requirements per 49 C.F.R. part 661

## SAMPLE PRINT LEGEND:

SOUTHWIRE [SYMBOL - LIGHTNING BOLT] #P# (UL/CSA) 1/C [#AWG or #kcmil] AL 420 MILS NL-EPR 35KV 133% INS LEVEL 25% TS MV-105 FOR CT USE SUN. RES. TC-ER(CSA 1/0 LARGER) FOR DIRECT BURIAL FT4 -ST1 YEAR (NESC) [SEQUENTIAL FEET MARKS]



Southwire Company, LLC | One Southwire Drive, Carrollton, GA 30119 | [www.southwire.com](http://www.southwire.com)



Southwire

**CABLETECH  
SUPPORT™**

Services

**Table 1 – Weights and Measurements**

| Stock Number | Cond. Size | Diameter Over Conductor | Diameter Over Insulation | Diameter Over Insulation Shield | Jacket Thickness <sup>1</sup> | Approx. OD | Approx. Weight | Max Pull Tension | Min Bending Radius | Conduit Size* |
|--------------|------------|-------------------------|--------------------------|---------------------------------|-------------------------------|------------|----------------|------------------|--------------------|---------------|
|              | AWG/Kcmil  | inch                    | inch                     | inch                            | mil                           | inch       | lb/1000ft      | lb               | inch               | inch          |
| TBA          | 1/0        | 0.336                   | 1.213                    | 1.273                           | 80                            | 1.453      | 985            | 634              | 17.4               | 4             |
| TBA          | 2/0        | 0.376                   | 1.253                    | 1.313                           | 80                            | 1.493      | 1049           | 799              | 17.9               | 5             |
| TBA          | 3/0        | 0.423                   | 1.300                    | 1.360                           | 80                            | 1.540      | 1127           | 1007             | 18.5               | 5             |
| TBA          | 4/0        | 0.475                   | 1.352                    | 1.412                           | 80                            | 1.592      | 1217           | 1270             | 19.1               | 5             |
| TBA          | 250        | 0.520                   | 1.406                    | 1.466                           | 80                            | 1.646      | 1308           | 1500             | 19.8               | 5             |
| TBA          | 350        | 0.616                   | 1.502                    | 1.562                           | 80                            | 1.742      | 1495           | 2100             | 20.9               | 5             |
| TBA          | 500        | 0.736                   | 1.622                    | 1.682                           | 110                           | 1.922      | 1856           | 3000             | 23.1               | 6             |
| TBA          | 600        | 0.813                   | 1.730                    | 1.790                           | 110                           | 2.030      | 2072           | 3600             | 24.4               | 6             |
| TBA          | 750        | 0.908                   | 1.825                    | 1.885                           | 110                           | 2.125      | 2311           | 4500             | 25.5               | 6             |
| TBA          | 1000       | 1.060                   | 1.977                    | 2.037                           | 110                           | 2.277      | 2702           | 6000             | 27.3               |               |
| TBA          | 1250       | 1.250                   | 2.171                    | 2.231                           | 110                           | 2.471      | 3141           | 7500             | 30                 |               |

All dimensions are nominal and subject to normal manufacturing tolerances

◊ Cable marked with this symbol is a standard stock item

\* Conduit size based on 3 phase 40% fill-factor without ground

<sup>1</sup> Comply with ICEA S-93-639 Appendix C for jacket thickness determination

**Table 2 – Electrical and Engineering Data**

| Cond. Size | DC Resistance @ 25°C | AC Resistance @ 90°C | Capacitive Reactance @ 60Hz | Inductive Reactance @ 60Hz | Zero Sequence Impedance* | Positive Sequence Impedance* | Shield Short Circuit Current 6 Cycles | Allowable Ampacity In Duct 90/105°C <sup>†</sup> | Allowable Ampacity In Air 90/105°C <sup>‡</sup> |
|------------|----------------------|----------------------|-----------------------------|----------------------------|--------------------------|------------------------------|---------------------------------------|--|---|
| AWG/Kcmil  | Ω/1000ft             | Ω/1000ft             | MΩ*1000ft                   | Ω/1000ft                   | Ω/1000ft                 | Ω/1000ft                     | Amp                                   | Amp  | Amp   |
| 1/0        | 0.168                | 0.211                | 0.069                       | 0.055                      | 0.550 + j0.280           | 0.212 + j0.055               | 4174                                  | 155/165  | 200/225   |
| 2/0        | 0.133                | 0.167                | 0.065                       | 0.053                      | 0.502 + j0.269           | 0.168 + j0.053               | 4304                                  | 175/190  | 230/260   |
| 3/0        | 0.105                | 0.132                | 0.061                       | 0.051                      | 0.462 + j0.257           | 0.133 + j0.051               | 4457                                  | 200/215  | 270/300   |
| 4/0        | 0.084                | 0.105                | 0.056                       | 0.050                      | 0.430 + j0.245           | 0.106 + j0.049               | 4626                                  | 230/245  | 310/345   |
| 250        | 0.071                | 0.089                | 0.054                       | 0.048                      | 0.409 + j0.233           | 0.090 + j0.048               | 4802                                  | 250/270  | 345/380   |
| 350        | 0.051                | 0.064                | 0.048                       | 0.046                      | 0.374 + j0.214           | 0.064 + j0.046               | 5114                                  | 305/330  | 430/475   |
| 500        | 0.035                | 0.045                | 0.043                       | 0.044                      | 0.343 + j0.194           | 0.046 + j0.044               | 5505                                  | 370/400  | 530/590   |
| 600        | 0.030                | 0.038                | 0.041                       | 0.043                      | 0.326 + j0.179           | 0.038 + j0.043               | 5856                                  | /  | /   |
| 750        | 0.024                | 0.030                | 0.038                       | 0.041                      | 0.310 + j0.166           | 0.031 + j0.041               | 6165                                  | 455/490  | 685/765   |
| 1000       | 0.018                | 0.023                | 0.034                       | 0.039                      | 0.290 + j0.149           | 0.024 + j0.039               | 6660                                  | 525/565  | 825/920   |
| 1250       | 0.0138               | 0.0204               | 0.029                       | 0.037                      | 0.264 + j0.131           | 0.014 + j0.037               | 7222                                  | 595/640  | 950/1055  |

\* Calculations are based on three cables triplexed / 5 mil 25 % over lapping copper tape shield Earth resistivity of 100 ohms-meter

<sup>†</sup> Ampacities are based on TABLE 310.60(C)(78) Detail 1. of the 2020 National Electrical Code (20°C Ambient Earth Temperature, Thermal Resistance ROH of 90)

<sup>‡</sup> Ampacities are based on TABLE 310.60(C)(70) of the 2020 National Electrical Code (40°C Ambient Air Temperature)

